

LIGHT INSIDE MULTISYSTEM

Dati tecnici - SENZAFINE

SENZAFINE - Technical data



A.A.G.

STUCCHI

Follow your illumination

DATI TECNICI RANGE DI PRODOTTO

PRODUCT RANGE TECHNICAL DATA

OPAL

CRI \geq 90

[mm]	n°. LED Mod	[K]	I LED [mA]	FLUSSO NOMINALE [lm] NOMINAL FLUX [lm]	FLUSSO REALE [lm] REAL FLUX [lm]	POTENZA [W] POWER [W]	POTENZA LED [W] POWER LED [W]	V _f	CRI	SDCM	LIFETIME [Khr]
286	1	3000	150	710	494,9	6,1	5,3	~ 36	\geq 90	\leq 3	>50Khr L90B5
567	2	3000	300	1420	989,7	11,4	10,6	~ 36	\geq 90	\leq 3	>50Khr L90B5
847	3	3000	450	2129	1484,6	17,2	15,9	~ 36	\geq 90	\leq 3	>50Khr L90B5
1128	4	3000	600	2839	1979,4	22,9	21,2	~ 36	\geq 90	\leq 3	>50Khr L90B5
1408	5	3000	750	3549	2474,3	28,8	26,5	~ 36	\geq 90	\leq 3	>50Khr L90B5

