

Luminaire

Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Measurem.


Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Luminaire Flux	389 lm	Luminaire Power	5.7 W	Efficacy	68.211 lm/W	Efficiency	100.00%
Source Flux	389 lm	Maximum value	4106.70 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	285 mm	Width	22 mm	Height	25 mm
Rectangular Luminous Area		Length	270 mm	Width	14 mm	Height	0 mm
Horizontal Luminous Area		0.003780 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000914 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		24-09-2018		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		389 lm	
Operator		1.18.27		Rated Voltage			
Temperature				Rated Current			
Humidity				Photocell			
Notes							

Luminaire Sources

Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
LED	LED		388.80	5.70	1
C.I.E.	92 98 100 100 100	D DIN 5040	A60		
F UTE	1.00 A	B NBN	BZ 1		


285mm x 22mm



C Halfplanes

180.0 0.0
270.0 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Measurem.


Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Luminaire Flux	389 lm	Luminaire Power	5.7 W	Efficacy	68.211 lm/W	Efficiency	100.00%
Source Flux	389 lm	Maximum value	4106.70 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.37	0.55	0.73	0.92	OC	0.18	0.36	0.55	0.73	0.91
OB	0.18	0.37	0.55	0.73	0.92	OD	0.18	0.36	0.55	0.73	0.91

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1596.68	1330.51	460.11	157.42	60.72	24.21	10.53	4.96	1.98	0.07
OB	1596.68	1330.51	460.11	157.42	60.72	24.21	10.53	4.96	1.98	0.07
OC	1596.68	1323.24	454.93	151.47	55.68	22.14	10.04	4.85	1.97	0.03
OD	1596.68	1323.24	454.93	151.47	55.68	22.14	10.04	4.85	1.97	0.03



H[m]	D[m]	Max lux	Med lux	Alpha=10.4°+10.4°	G=0.0	
1.00	0.37	1597	998			
2.00	0.73	399	249			
3.00	1.10	177	111			
4.00	1.47	100	62			
5.00	1.83	64	40			

H[m]	D[m]	Max lux	Med lux	Beta=10.3°+10.3°	G=0.0	
1.00	0.36	1597	998			
2.00	0.73	399	249			
3.00	1.09	177	111			
4.00	1.46	100	62			
5.00	1.82	64	40			

Luminaire

Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°


Measurem.

Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Luminaire Flux	389 lm	Luminaire Power	5.7 W	Efficacy	68.211 lm/W	Efficiency	100.00%
Source Flux	389 lm	Maximum value	4106.70 cd/klm	Position	C=0.00 G=0.00	CG Double Symmetrical	

Isolux (Floor)

Luminaire position X=0.00m Y=0.00m Z=2.50m



Luminaire

Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Measurem.

Code M22286-3-A-E
Name M22 285 mm 3000K CRI95 LENTE 20°

Luminaire Flux	389 lm	Luminaire Power	5.7 W	Efficacy	68.211 lm/W	Efficiency	100.00%
Source Flux	389 lm	Maximum value	4106.70 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Working Plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions	Lateral View					Viewed Endwise				
x=2H y=2H	13.9	14.6	14.2	14.8	15.0	13.6	14.3	13.8	14.5	14.7
x=2H y=3H	14.2	14.9	14.5	15.1	15.3	13.9	14.6	14.2	14.8	15.0
x=2H y=4H	14.3	14.9	14.6	15.2	15.4	14.0	14.7	14.3	14.9	15.2
x=2H y=6H	14.3	14.9	14.7	15.2	15.5	14.0	14.6	14.4	14.9	15.2
x=2H y=8H	14.3	14.8	14.6	15.1	15.4	14.0	14.6	14.3	14.8	15.1
x=2H y=12H	14.3	14.8	14.6	15.1	15.4	14.0	14.5	14.3	14.8	15.1
x=4H y=2H	14.0	14.6	14.3	14.9	15.1	13.7	14.3	14.0	14.6	14.8
x=4H y=3H	14.4	15.0	14.8	15.3	15.6	14.2	14.7	14.5	15.0	15.3
x=4H y=4H	14.6	15.0	15.0	15.4	15.7	14.3	14.8	14.7	15.1	15.5
x=4H y=6H	14.6	15.0	15.0	15.4	15.8	14.4	14.8	14.8	15.1	15.5
x=4H y=8H	14.6	14.9	15.0	15.3	15.7	14.4	14.7	14.8	15.1	15.5
x=4H y=12H	14.6	14.9	15.0	15.3	15.7	14.3	14.6	14.8	15.0	15.4
x=8H y=4H	14.6	14.9	15.0	15.3	15.7	14.4	14.7	14.8	15.1	15.5
x=8H y=6H	14.7	14.9	15.1	15.3	15.8	14.4	14.7	14.9	15.1	15.5
x=8H y=8H	14.6	14.8	15.1	15.3	15.7	14.4	14.6	14.9	15.0	15.5
x=8H y=12H	14.6	14.8	15.1	15.2	15.7	14.3	14.5	14.8	15.0	15.5
x=12H y=4H	14.6	14.9	15.0	15.3	15.7	14.3	14.6	14.7	15.0	15.4
x=12H y=6H	14.6	14.8	15.1	15.3	15.7	14.4	14.6	14.8	15.0	15.5
x=12H y=8H	14.6	14.8	15.1	15.2	15.7	14.4	14.5	14.8	15.0	15.5

Luminaire

Code M22286-3-A-E
 Name M22 285 mm 3000K CRI95 LENTE 20°

Measurem.

Code M22286-3-A-E
 Name M22 285 mm 3000K CRI95 LENTE 20°

Luminaire Flux	389 lm	Luminaire Power	5.7 W	Efficacy	68.211 lm/W	Efficiency	100.00%
Source Flux	389 lm	Maximum value	4106.70 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical

	45°	50°	55°	60°	Average Luminance		75°	80°	85°	
0.0°	9057	6525	4858	3805	65°	3103	2610	2022	1126	209
90.0°	8284	6086	4633	3685	70°	3037	2564	2017	1060	96

Flush mounted or longitudinal view												
		Illumination(lx)										
A	A	2000	1000	750	500		<300					1.15
B	1		2000	1500	1000	750	500	<300				1.5
C					2000		1000	500	<300			1.85
D	2						2000	1000	500	<300		2.2
E	3							2000	1000	500	<300	2.55

