



Modulo di luce lineare a 48V. Fissaggio meccanico. Per binari 9500 MULTISYSTEM® EVO. Riflettore UGR in policarbonato. Cover in poliammide. L(mm): 1125. 3000K. CRI≥95 R9-80: LED.  
48V linear light module. Mechanical fixing. For 9500 MULTISYSTEM® EVO tracks. Polycarbonate UGR reflector. Polyamide cover. L(mm): 1125. 3000K. CRI≥95 R9-80: LED.



48V



IP20

RG1

unlimited



Real Flux (lm):	1651,7*
Nominal Flux (lm):	2017
Real Power (W):	21,2* ±10%
Efficiency (lm/W):	77,9*
LED source:	LED
Colour Temperature (K):	3000
CRI:	≥95
MacAdam:	≤3
Beam Angle:	67,4°
UGR	<19
Lifetime (Khr):	>50 L90B10
Driver:	ON-OFF / 0...10V / DALI SELV
V <sub>F</sub> :	~ 18
I LED (mA):	1000
L (mm):	1125
Weight (g):	770
Materials:	Corpo in alluminio + riflettore UGR in policarbonato + cover in poliammide Aluminium body + polycarbonate UGR reflector + polyamide cover
Colour:	Nero gofrato / Black embossed - Bianco gofrato / White embossed
Mounting:	Meccanico / Mechanical
Packaging:	Tubo / Tube



Room (m): 4x4x3h H luminaire (m): 2,5 Ref. surface: floor

Altre temperature colore e CRI disponibili su richiesta. I valori contrassegnati con l'asterisco (\*) sono valori di misurazione che si riferiscono a una temperatura ambiente di 25°C salvo diversa specifica. Nel corso del tempo il flusso luminoso subisce un inevitabile calo dovuto alla tecnologia. A.A.G. Stucchi si riserva la facoltà di apportare modifiche tecniche senza preavviso.  
Other colour temperatures and CRI available upon request. All values marked with an (\*) are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Luminous flux is subject to a normal technology drop over time. A.A.G. Stucchi reserves the right to make technical changes without prior notice.