

Salient features

- High flexibility. Cisca is your perfect indoor companion.
- DALI-2 support.
- Many different options to chose from in terms of colors, fixed/adjustable and cutout sizes.
- High CRI up to CRI 80 or 90.
- Various dimming options i.e. DALI-2 / Wireless / 1-10V. Electronic controlgear from Helvar, Finland.
- Color temperature options: 3000, 4000K. Others available on request.
- Optics: narrow, medium and wide. Asymmetric for adjustable versions

Electronic control
gear from

Helvar

Stylish and efficient!



cisca 70 round

specifications sheet

LUXTRON
S Y S T E M S

Stylish and efficient!


DISCLAIMER

All values marked in this document rated values. Luxtron uses tested products and components from leading component manufactures, however there may be isolated instances of technology related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Color temperature is subject to a tolerance of up to ± 150 Kelvin from nominal value. These values apply to an ambient temperature of 25°C



Electronic control gear from

Helvar



Technical Data

Load Wattage	7 W 10 W (max)
Input Voltage	220 - 240 V 50 - 60 Hz
Beam Angle	15° / 24° / 38°
Luminous Flux	533 lumens @ 7 W
Color Temperature	3000 / 4000 K others available on request
Color Rendering Index	80 / 90
Dimming Protocols	DALI-2 / Wireless / 1-10V Phase-Dim
Cut out size	Φ 65 mm
Dimensions & IP Rating	Φ 70 x H77 mm IP 40
Reflector Colors	Silver, Gold, Red, Black, White

Dimensions

