

SNAPPY

Downlights for low ceilings

LUXTRON
SYSTEMS



*Multiple power and
size configurations for
low ceiling applications!*

SNAPPY

Low UGR for low height ceilings

LUXTRON
SYSTEMS

SNAPPY offers multiple different configurations based on power and sizes to accommodate areas where the ceiling height of the space is a concern.

Available in 3 different cutouts, SNAPPY offers itself as the perfect choice for low ceiling areas whilst offering good light quality and no-flicker.



Electronic control gear from

Helvar

Chip On-Board technology from

CITIZEN

Technical Data

System Wattages (A) D60 mm (B) D80 mm (C) D100 mm (based on diameter)	(A) 6 W (B) 10 W (C) 15/20 W
Input Voltage	220 - 240V AC (50-60 Hz)
Beam Angle	15° / 24° / 36° / 50°
Luminous Flux (@ 4000K)	-
Color Temperature	2700 / 3000 / 3500 / 4000 K Tunable White Dim to Warm others available on request
Color Rendering Index	80 / 90 / 97
Dimming Protocols	DALI-2 / Wireless / 1-10V

Salient features

- Starts from 6 W upto 20 W.
- Easy 3.5mm jack connector supplied with pre-wired Helvar LED driver allows for tension-free connection and eliminates any human error at site.
- Low UGR.
- Die cast aluminium heatsink with highly efficient heat dissipation ensures long life of the LED engine.
- Equipped with LED components from **Helvar & latest 6/8th Generation Citizen COBs**
- Various dimming options i.e. DALI-2 / Wireless / 1-10V.
Electronic controlgear from Helvar, Finland.
- Color temperature options: **2700, 3000, 4000K, Dim to Warm, Tunable White.** Others available on request.



Dimensions and Cutouts	D60 H42 mm D80 H50 mm D100 H62 mm	Ø 55 mm Ø 75 mm Ø 95 mm
IP Rating	IP20 rated (for indoor use only)	