

*lighting up every
detail!*



Lighting every detail

Glitz is our low wattage (1-3W) adjustable spot family to highlight every detail ideally for showcase lighting in retail stores, such as jewelry or watch stores.

Glitz comes in 2 different formats:


- **GLITZ STANDALONE 12/24/48/240V**
Standalone surface mounted unit with adjustable height with options to dim or connect with a suitable battery system.
- **GLITZ MICRO 48V**
Track mounted unit to be used either on linear or curved MICRO 48V track system



Electronic control
gear from

Helvar  *Entity*[®]

Compatible with MICRO
track system



A.A.G.
STUCCHI

EUTRAC

Single spot for MICRO track and display lighting



GLITZ 2350

technical details



Electronic control
gear from

Helvar
 *Entity*®

Compatible with
MICRO track system

A.A.G.
STUCCHI

EUTRAC

Technical Data

System Wattage	3 W
Input Voltage	230V AC (Standalone version) 12V / 24V DC (To use with battery) 48V DC (for MICRO track)
Lumen Output	245 lumens
Beam Angle	60°
Color Temperature	2700 / 3000 / 3500 / 4000 K others available on request
Color Rendering Index	>= 80 / 90
Dimming Protocols	DALI-2 / Wireless Dimmer on Lamp
Dimensions	D23 H50 mm
IP Rating	IP 20 rated, for indoor use only
Pole length and Drill size	Adjustable b/w 100 - 400 mm, drill size - D12 mm
Color finishes	Black / Silver others on request

Salient features

- Made from die cast aluminum.
- Glitz comes in 2 versions either as a standalone unit with adjustable pole or for a 48V DC track system.
- Compatible with MICRO track system from A.A.G. Stucchi / Eutrac.
- Available in both with fixed optics as well as zoomable optics.
- Equipped with LED components from **Helvar**.
- Various dimming options i.e. DALI-2 / Wireless.
- Color temperature options ranging from 2700K, 3000K, 4000K, 6000K, others options available on request.
- CRI80 is a standard. CRI90 is available on request.