

SPAN02

Cylinder downlight family

LUXTRON
SYSTEMS



*Same cylinder, now
upgraded!*

SPAN02 P

Pendant downlight family

LUXTRON
SYSTEMS

SPAN02 is the upgraded and updated version from our simple cylindrical shape in SPANO.

Equipped with 6 different reflector colors, 2 mounting options and 2 optic options, it completes our previous SPANO range.

Suitable for indoor lighting applications namely in commercial and residential spaces.

*Same cylinder,
now upgraded!*



Chip On-Board
technology from

CITIZEN

Technical Data

Load Wattage	12 / 15 W 20 / 25 W 30 W
Input Voltage	220 - 240V AC (50-60 Hz)
Beam Angle	20° / 40°
Mounting Options	Suspended / Pendant (P)
Color Temperature	2700 / 3000 / 3500 / 4000 K Dim to Warm others available on request
Color Rendering Index	80 / 90
Dimming Protocols	DALI-2 / 1-10V
Dimensions (A) 12W / 15W (B) 20W / 25W (C) 30W	(A) D75 H152 mm (B) D95 H152 mm (C) D115 H152 mm

Salient features

- Starts from 12W upto 30W.
- Pendant downlight range
- Equipped with LED components from **Helvar & latest 6/8th Generation Citizen COBs**
- Various dimming options i.e. DALI-2 / Wireless / 1-10V.
Electronic controlgear from Helvar, Finland.
- Color temperature options: **2700, 3000, 4000K**. Others available on request.
- 6 different reflector colors to meet needs of different occasions

Reflector colors	Black (B) Matt White (W) Silver (S) Champagne Gold / Gold (CG/G) Nickel (or Gun Black) (N)
Body colors	Black (B) / White (W)
IP Rating	IP20 for indoor use only

SPAN02 SM

Surface mounted downlight family

SPAN02 is the upgraded and updated version from our simple cylindrical shape in SPANO.

Equipped with 6 different reflector colors, and 2 optic options, it completes our previous SPANO range.

Suitable for indoor lighting applications namely in commercial and residential spaces.

*Same cylinder,
now upgraded!*

Electronic control
gear from

Helvar

Chip On-Board
technology from

CITIZEN

Technical Data

Load Wattage	12 / 15 W 20 / 25 W 30 W 35 W 45 W
Input Voltage	220 - 240V AC (50-60 Hz)
Beam Angle	20° / 40°
Mounting Options	Surface Mounted (SM)
Color Temperature	2700 / 3000 / 3500 / 4000 K Dim to Warm others available on request
Color Rendering Index	80 / 90
Dimming Protocols	DALI-2 / 1-10V
Dimensions (A) 12W / 15W (B) 20W / 25W (C) 30W (D) 35W (E) 45W	(A) D75 H152 mm (B) D95 H152 mm (C) D115 H152 mm (D) D140 H162 mm (E) D170 H182 mm

Salient features

- Starts from 12W upto 45W.
- Surface mounted downlight range
- Equipped with LED components from **Helvar & latest 6/8th Generation Citizen COBs**
- Various dimming options i.e. DALI-2 / Wireless / 1-10V.
Electronic controlgear from Helvar, Finland.
- Color temperature options: **2700, 3000, 4000K.** Others available on request.
- 6 different reflector colors to meet needs of different occasions

Reflector colors	Black (B) Matt White (W) Silver (S) Champagne Gold / Gold (CG/G) Nickel (or Gun Black) (N)
Body colors	Black (B) / White (W)
IP Rating	IP20 for indoor use only

